



# MARINI AUTOGAS

marini@mariniautogas.com

Ph +39 0444 349700 - ITALY

## RINGAS SEQUENTIAL REDUCER ECE 67R-01

Mod: **RINGAS**

Weight: kg 1.4

Dimension: mm 93X91



## Technical Specifications

		RINECO	RINGAS	RINGAS PLUS
POWER ENGINE	Power	Up to 100Kw	Up to 140Kw	Up to 200Kw
	Minimum temperature	-40°	-40°	-40°
	Engine	4cyl	4/6cyl	6/8cyl
HEAT EXCHANGE	All over surfaces	♦	♦	♦
	Single room with O-Rings	♦	♦	♦
	Single room with O-Rings and Safety Block(min.q.ty 100pcs)		♦	♦
	Water temperature 120°	♦	♦	♦
PRE-HEATING ROOMS	Two rooms before expansion high pressure	♦	♦	♦
CALIBRATION	Before and after high pressure	♦	♦	♦
ADJUSTMENT	Screw adjustment for exit pressure from 0.8 up to 2.2bar	♦	♦	♦
COMPENSATION ROOM	Vacuum	♦	♦	♦
DIAPHRAGM	It is not in direct contact with LPG so to maintain unchanged characteristics along the time	♦	♦	♦
OVER PRESSURE	On request	♦	♦	♦
CONNECTIONS	Water Ø 16 : right connection	♦		
	Water Ø 16 : adjustable connection in brass	♦	♦	♦
	LPG exit: Ø 12	♦	♦	♦
	LPG entry: Ø 6	♦	♦	
	LPG entry: Ø 8		♦	♦
DIMENSION	mm 93x91	♦	♦	♦
WEIGHT	Kg. 1.4	♦	♦	♦
MATERIALS	Aluminium – brass- Viton - HNBR	♦	♦	♦
FIXING	In three points with metal bracket	♦	♦	♦
APPROVAL	ECE 67R-01	♦	♦	♦
NOTE:	Possibility to realize the first stage in brass material so to optimize heat exchange.			♦
	Usable with main ECU systems present on the market	♦	♦	♦